

IN THE CLAIMS

1. (Currently Amended) An oven apparatus, comprising:

a housing;

a heat generator disposed in association with the housing;

a code input device;

a controller that stores a plurality of recipe programs upon receipt of the plurality of programs and operates the heat generator in accordance with a recipe program selected from the plurality of recipe programs in view of a code input by the code input device; and

β1 a network interface, in communication with the controller, that requests a recipe program from an operably connected, but external device and receives the requested recipe program.

2. (Original) The oven apparatus of claim 1, further comprising:

a clock in communication with the controller, the clock being set upon receipt of a time synchronization message at the network interface.

3. (Original) The oven apparatus of claim 1, wherein a recipe program request message is formatted upon the controller failing to associate the input code from the code input device with one recipe program from the plurality of recipe programs.

4. (Original) The oven apparatus of claim 3, wherein the network interface is in receipt of a new recipe program associated with the input code in response to the recipe program request message being sent to the operably connected, but external device.

5. (Currently Amended) A method, comprising:
receiving, without user intervention, in an oven a plurality of recipe programs at a network interface from an operably connected, but external device; and
storing the plurality of recipe programs in a memory by a controller that are each selectable with a digital signal from a code input device; and
configuring the oven in response to the digital signal being associated with one recipe program in the plurality of recipe programs.

6. (Currently Amended) The method of claim 5, further comprising:
formatting a recipe program request message in response to the controller failing to select a recipe program from the plurality of recipe programs that is associated with the digital signal;
and
receiving a requested recipe program at the network interface from ~~an~~ the operably connected, but external device in response to the recipe program request message.

7. (Original) The method of claim 5, further comprising:
receiving a time synchronization message at the network interface; and
setting a clock in the oven by the controller upon receipt of the time synchronization message.

8. (Currently Amended) An apparatus, comprising:

means for receiving, without user intervention, in an oven a plurality of recipe programs at a network interface from an operably connected, but external device; and

means for storing the plurality of recipe programs in a memory by a controller that are each selectable with a digital signal from a code input device; and

means for configuring the oven in response to the digital signal being associated with one recipe program in the plurality of recipe programs.

β1 9. (Currently Amended) The apparatus of claim 8, further comprising:

means for formatting a recipe program request message in response to the controller failing to select a recipe program from the plurality of recipe programs that is associated with the digital signal; and

means for receiving a requested recipe program at the network interface from the operably connected, but external device in response to the recipe program request message.

10. (Original) The apparatus of claim 8, further comprising:

means for receiving a time synchronization message at the network interface; and

means for setting a clock in the oven by the controller upon receipt of the time synchronization message.

11. (Currently Amended) A machine-readable signal-bearing medium containing instructions that cause a system to perform a method for operating an oven, the method comprising:

receiving, without user intervention, at the oven a plurality of recipe programs at a network interface from an operably connected, but external device; and

storing the plurality of recipe programs in a memory by a controller that are each selectable with a digital signal from a code input device; and

configuring the oven in response to the digital signal being associated with one recipe program in the plurality of recipe programs.

12. (Currently Amended) The machine-readable signal-bearing medium of claim 11, further comprising:

formatting a recipe program request message in response to the controller failing to select a recipe program from the plurality of recipe programs that is associated with the digital signal; and

receiving a requested recipe program at the network interface from ~~an~~ the operably connected, but external device in response to the recipe program request message.

13. (Previously Presented) The machine-readable signal-bearing medium of claim 11, further comprising:

receiving a time synchronization message at the network interface; and
setting a clock in the oven by the controller upon receipt of the time synchronization message.

14. (New) The oven apparatus of claim 1, wherein the code input device comprises a bar code reader for scanning a unique product code.

15. (New) The method of claim 5, wherein the code input device comprises a bar code reader for scanning a unique product code.

16. (New) The apparatus of claim 8, wherein the code input device comprises a bar code reader for scanning a unique product code.

17. (New) The machine-readable signal-bearing medium of claim 11, wherein the code input device comprises a bar code reader for scanning a unique product code.

18. (New) An oven apparatus, comprising:

a housing;

a heat generator disposed in association with the housing;

a code input device including a bar code reader for scanning a unique product code; and

a controller that stores a plurality of recipe programs upon receipt of the plurality of programs and operates the heat generator in accordance with a recipe program selected from the plurality of recipe programs in view of a code input by the code input device, the plurality of recipe programs being received at a network interface from an operably connected, but external device.

19. (New) A method, comprising:
receiving in an oven a plurality of recipe programs at a network interface from an operably connected, but external device; and
storing the plurality of recipe programs in a memory by a controller that are each selectable with a digital signal from a code input device, the code input device including a bar code reader for scanning a unique product code; and
configuring the oven in response to the digital signal being associated with one recipe program in the plurality of recipe programs.

20. (New) The method of claim 19, further comprising:
formatting a recipe program request message in response to the controller failing to select a recipe program from the plurality of recipe programs that is associated with the digital signal;
and
receiving a requested recipe program at the network interface from the operably connected, but external device in response to the recipe program request message.
